


PART NUMBER:
i2350-G-XX-2J

NOTES:
1) SPC GR-326 GEOMETRIC
REQUIREMENTS =>PROTRUSION/UNDERCUT:+50/-100nm

PERFORMANCE SPECIFICATIONS	
FIBER TYPE: MULTIMODE (50/125um)	
	850/1310nm
INSERTION LOSS	0.3dB
TYPICAL INSERTION LOSS	0.2dB
MATING DURABILITY (500 cycles)	<0.2dB
TEMPERATURE RANGE	-40° C to 85° C



OM3

ITEM	QTY.	DESCRIPTION	PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF IFIBER OPTIX, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION IS PROHIBITED.	DRAWN BY: LJUS	DATE: JAN-02-2007	 IFIBER OPTIX, INC. 14450 CHAMBERS RD. TUSTIN, CA 92780 www.ifiberoptix.com Tel: 714-665-9796 Fax: 714-665-9757	
1	4	LC DUPLEX MULTIMODE 127um CONNECTOR		CHECKED BY: SANIEEV	DATE: JAN-02-2007		
2	1	CORNING MULTIMODE DUPLEX 50/125um, 10-GIG AQUA 2mm		APPROVED BY: SANIEEV	DATE: JAN-02-2007		
3	1	N/A		TITLE: LC-LC MM DX			PART NUMBER: i2350-G-XX-2J
4		N/A		50/125um 10-GIG 2mm			